

Serial Number
WAN IP Address
Connected At Fri Jul 17th 2015 12:34:03
Inform Events 0 BOOTSTRAP, 1 BOOT, !INITIAL_CONTACT, !FIRMWARE_UPGRADED
Hardware Version B2
Software Version 0.0.9.4P3
Session ID 88BAD43FEE33D40153200BE30EDF3B10.main

Time	Type	Event Detail
+0.023s	SOAP XML	3454 bytes received from device
<pre> <?xml version="1.0" encoding="UTF-8"?> <cwmp:Inform xmlns:cwmp="urn:dsiforum-org:cwmp-1-2" xmlns:soap_enc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:soap_env="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org /2001/XMLSchema-instance"> <DeviceId> <Manufacturer>SmartRG</Manufacturer> <OUI>00236A</OUI> <ProductClass>SR400ac</ProductClass> <SerialNumber>00236AA37BC5</SerialNumber> </DeviceId> <Event soap_enc:arrayType="cwmp:EventStruct[2]"> <EventStruct> <EventCode>0 BOOTSTRAP</EventCode> <CommandKey/> </EventStruct> <EventStruct> <EventCode>1 BOOT</EventCode> <CommandKey/> </EventStruct> </Event> <MaxEnvelopes>1</MaxEnvelopes> <CurrentTime>2015-07-17T12:34:02-07:00</CurrentTime> <RetryCount>2</RetryCount> <ParameterList soap_enc:arrayType="cwmp:ParameterValueStruct[18]"> <ParameterValueStruct> <Name>Device.DeviceInfo.Description</Name> <Value xsi:type="xsd:string">Gigabit Residential Gateway</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.DeviceCategory</Name> <Value xsi:type="xsd:string">Router</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.HardwareVersion</Name> <Value xsi:type="xsd:string">B2</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.Manufacturer</Name> <Value xsi:type="xsd:string">SmartRG</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.ManufacturerOUI</Name> <Value xsi:type="xsd:string">00236A</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.ModelName</Name> <Value xsi:type="xsd:string">SR400ac</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.ModelNumber</Name> <Value xsi:type="xsd:string">SR400ac</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.ProductClass</Name> <Value xsi:type="xsd:string">SR400ac</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.ProvisioningCode</Name> <Value xsi:type="xsd:string"/> </ParameterValueStruct> <ParameterValueStruct> </pre>		

Time	Type	Event Detail
		<pre> <Name>Device.DeviceInfo.SerialNumber</Name> <Value xsi:type="xsd:string">00236AA37BC5</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.DeviceInfo.SoftwareVersion</Name> <Value xsi:type="xsd:string">0.0.9.4P3</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.GatewayInfo.ManufacturerOUI</Name> <Value xsi:type="xsd:string">00236A</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.GatewayInfo.ProductClass</Name> <Value xsi:type="xsd:string">SR400ac</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.GatewayInfo.SerialNumber</Name> <Value xsi:type="xsd:string">00236AA37BC5</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.ManagementServer.ConnectionRequestURL</Name> <Value xsi:type="xsd:string">http://192.168.25.105:7547/</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.RootDataModelVersion</Name> <Value xsi:type="xsd:string">2.4</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.Time.CurrentLocalTime</Name> <Value xsi:type="xsd:string">2015-07-17T12:34:03-0700</Value> </ParameterValueStruct> <ParameterValueStruct> <Name>Device.Time.LocalTimeZone</Name> <Value xsi:type="xsd:string">PST8PDT,M3.2.0,M11.1.0</Value> </ParameterValueStruct> </ParameterList> </cwmp:Inform> </pre>
+0.066s	Fire Event	REBOOT
+0.118s	Fire Event	INITIAL_CONTACT
+0.153s	Fire Event	FIRMWARE_UPGRADED
+0.155s	SOAP XML	453 bytes sent to device
		<pre> <soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:soap-enc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:cwmp="urn:dsforum-org:cwmp-1-0" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"> <soap:Header> <cwmp:ID soap:mustUnderstand="1">3</cwmp:ID> </soap:Header> <soap:Body> <cwmp:InformResponse> <MaxEnvelopes>1</MaxEnvelopes> </cwmp:InformResponse> </soap:Body> </soap:Envelope> </pre>
+0.242s	SOAP XML	54 bytes received from device
		<pre> <?xml version="1.0" encoding="UTF-8" standalone="no"?> </pre>
+0.301s	Script Begin	Initial Configuration
+0.364s	Script Log Message	[INFO] pushAppCodes[ManagementServer], pullAppCodes[]
+0.545s	Script Log Message	[ERROR] NODRIVER: Unable to push ManagementServer. there is no driver
+0.552s	Script Completed	
+0.624s	Script Begin	Subscriber Association
+0.691s	Script Log Message	[INFO] pushAppCodes[PPP,SR,PF,CAPO,NTFY], pullAppCodes[]
+1.338s	Script Log Message	[ERROR] NODRIVER: Unable to push PF. there is no driver
+1.373s	Script Log Message	[ERROR] NODRIVER: Unable to push PPP. there is no driver
+1.407s	Script Log Message	[ERROR] NODRIVER: Unable to push NTFY. there is no driver
+1.434s	Script Log Message	[ERROR] NODRIVER: Unable to push SR. there is no driver

Time	Type	Event Detail
+1.453s	Script Log Message	[ERROR] NODRIVER: Unable to push CAPO. there is no driver
+1.455s	Script Completed	
+1.515s	Script Begin	Firmware Updated
+1.571s	Script Log Message	[INFO] pushAppCodes[], pullAppCodes[FirmwareManagementStatus]
+1.748s	Script Log Message	[ERROR] NODRIVER: Unable to pull FirmwareManagementStatus. there is no driver
+1.777s	Script Completed	
+1.805s	Fire Event	INFORM